

SCC #39 APPROVED 29 FEB 00
MIL-STD-188-220B
Topology Update Data Structure

Redlined

6.3.4 Intranet layer.

- d. In the Topology Update Data Structure (Figure 28), the "node address" and "node predecessor address" (see 5.4.1.2.3 and 5.4.1.2.5, respectively) have been implemented in the INC and the IDM in the following manner:

Both of these addresses are "the link address of the node in the Intranet". The link address is seven bits long (see 5.3.4.2.2.1). ~~The C/R bit associated with this link address is not required by the Intranet Layer.~~ As such, bits 0 through 6 contain the "link address" used in the node address and node predecessor address. Bit 7 must be zero. Note: Neither the C/R bit nor and the extension bit associated with the link address is will not be used in the Topology Update Data Structure.

Changes Applied

6.3.4 Intranet layer.

- d. In the Topology Update Data Structure (Figure 28), the "node address" and "node predecessor address" (see 5.4.1.2.3 and 5.4.1.2.5, respectively) have been implemented in the INC and the IDM in the following manner:

Both of these addresses are "the link address of the node in the Intranet". The link address is seven bits long (see 5.3.4.2.2.1). As such, bits 0 through 6 contain the "link address" used in the node address and node predecessor address. Bit 7 must be zero. Note: The C/R bit and the extension bit associated with the link address will not be used in the Topology Update Data Structure.